

# 2MP Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera

## DH-H2A



#### **Series Overview**

The Hero Series, which is under the Dahua Wireless series, are cameras that are not only easy to install and operate, but also perform outstandingly and are cost-effective. These highly sensitive cameras deliver crystal clear images and offer 360-degree monitoring without blind spots. Their powerful functions, such as human detection and auto tracking, not only assist with the accurate detection and continuous tracking of targets, but also reduce the occurrence of false alarms. It also features two-way talk, which allows you to freely communicate with your scene anytime, anywhere. Information is synchronously sent to your phone to keep you up-to-date. These cameras are widely used in small scenes such as shops and restaurants.



#### 2MP

Clear images with sharp details



#### One Camera for 360° View

360° monitoring without blind spots



#### **Human Detection**

Focuses on what matters and reduces false alarms



#### Day&Night

Clear images even at night



#### **Auto Tracking**

Automatic tracking of targets



#### **Two-way Talk**

Communication anytime, anywhere



#### **One-click Privacy Mode**

Protects your privacy



#### H.265

Advanced H.265 compression technology



#### **DMSS App**

Easy to use



#### Micro SD Card

Low-cost storage



### **Upgrade Your Experience with DMSS**

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.









## **Specifications**

#### Camera

1/3.2" CMOS Image Sensor

1920 (H) × 1080 (V) Max. Resolution

Electronic Shutter Speed Auto/Manual 1/3 s-1/100,000 s

Illumination Distance Up to 10 m (32.81 ft) (IR)

Illuminator On/Off Control Auto Illuminator Number 1 (IR LED) Pan: 0° to 355°; Angle Adjustment Tilt:-5° to +80°

Max. Aperture 3.6 mm: F2.0

Field of View 3.6 mm: H: 79°; V: 43°; D: 94°

#### Video & Audio

WDR

Video Compression H.265

Main stream: 1920 × 1080 @25 fps Video Frame Rate Sub stream: 640 × 480 @25 fps

DWDR

Resolution 1080p (1920 × 1080); VGA (640 × 480)

Video Bit Rate H.265: 80 kbps-4096 kbps

Day/Night Auto(ICR)/Color/B/W

Motion Detection OFF/ON 0°/180° Image Rotation

Built-in MIC Yes, built-in Mic Built-in Speaker Yes, built-in speaker

Audio Compression G.711a

#### **Alarm**

No SD card; SD card full; SD card error; network Alarm Event disconnection; motion detection; audio detection

**Network** 

Network Port RJ-45 (10/100 Base-T)

Wi-Fi IEEE 802.11b/g/n 2.4-2.4835 GHz, 2.4 G

Storage Micro SD card (up to 256 GB)

Management Software DMSS

Mobile Client iOS;Android

General

Certifications CE

Power Supply 5 VDC, 1A

Max. (video stream acquiring + IR + PTZ Rotation): 3.5 W Power Consumption

Operating Temperature -10 °C to +45 °C (+14 °F to +113 °F)

Operating Humidity ≤ 95% Casing Material

**Product Dimensions** φ77.8 mm × 108.1 mm (φ3.06" × 4.26")

204.2 g (0.45 lb) Net Weight

## What's in the box



Tools:

Installation Position Map×1

Mounting Plate×1 Screw Package×1

Documents: QR Code×1

Quick Start Guide×1 Legal and regulation information×1

Power:

Power Adapter×1



